

Effective pixels	18.1 million
Image sensor	1/2.3-in. type CMOS; total pixels: Approx. 18.91 million
Lens	NIKKOR lens with 14x optical zoom; 4.5-63.0 mm (35mm [135] format equivalent: 25-350 mm); f/3.3-5.9
Digital zoom magnification	Up to 2x (35mm [135] format equivalent: Approx. 700 mm)
Focus range*1	[W]: Approx. 50 cm (1 ft 8 in.) to ∞, Macro mode: Approx. 1 cm (0.4 in.) to ∞
Monitor	7.5 cm (3-in.), Approx. 460k-dot, TFT LCD monitor with anti-reflection coating
Storage media	SD/SDHC/SDXC memory cards*5
Image size (pixels)	18M (High) [4896 x 3672★], 18M [4896 x 3672], 8M [3264 x 2448], 4M [2272 x 1704], 2M [1600 x 1200], VGA [640 x 480], 16:9 [4896 x 2754], 1:1 [3672 x 3672]
Vibration Reduction (VR)	Lens shift
Motion blur reduction	Motion detection (still pictures)
ISO sensitivity (Standard output sensitivity)*2	ISO 125-1600 (Auto), ISO 3200 (Manual setting is enabled in Auto mode)
Interface	Hi-Speed USB
Power sources	Two LR6/L40 (AA-size) alkaline batteries (supplied), Two FR6/L91 (AA-size) lithium batteries (optional), Two EN-MH2 rechargeable Ni-MH batteries (optional), EH-65A AC Adapter (optional), MH-72/MH-73 Battery Charger (optional)
Battery life of still shooting*3	Approx. 150 shots with alkaline, 660 shots with lithium*6, or 410 shots with EN-MH2 batteries
Dimensions	Approx. 108.3 x 68.7 x 34.1 mm (4.3 x 2.8 x 1.4 in.) excluding projections*7

Dimensions (W x H x D)	Approx. 288.5 x 99.7 x 57.1 mm (4.5 x 2.0 x 2.3 in.) Excluding projections
Weight	Approx. 237 g (8.4 oz.) with battery and SD memory card*7
Supplied accessories*4	Two LR6/L40 (AA-size) alkaline batteries, UC-E16 USB Cable, AN-CP19 Camera Strap, ViewNX 2 CD
Optional accessories	Two EN-MH2 rechargeable Ni-MH batteries, EH-65A AC Adapter, MH-72/MH-73 Battery Charger, EG-CP16 Audio Video Cable, AN-CP23 Camera Strap

\*1 All distances measured from center of front surface of lens.

\*2 Depending on the conditions, certain settings may not be configured.

\*3 Based on CIPA industry standard for measuring life of camera batteries. Measured at 23°C (+/-3°C); zoom adjusted with each shot, built-in flash fired with every other shot, image mode set to Normal. In a cold environment, the number of shots may decrease according to the battery characteristics.

\*4 Supplied accessories may differ by country or area.

\*5 Not compatible with Multi Media Cards (MMC).

\*6 In case of using two AA Energizer® Ultimate Lithium batteries.

\*7 Method of noting dimensions and weight is in accordance with CIPA DCG-002-2012 guideline.

Specifications are subject to change without any notice or obligation on the part of the manufacturer.