

▼ Type

Type	Single-lens reflex digital camera
Lens Mount	Nikon F bayonet mount

▼ Image Sensor

Picture Angle	Nikon DX format (Effective picture angle 1.5x [Approx.] conversion factor)
Effective Pixels	24.2 million
Sensor Size	23.5 mm x 15.6 mm
Image Sensor Format	DX
Image Sensor Type	CMOS
Total Pixels	24.7 million
Dust-reduction system	Image sensor cleaning
Dust-Off Reference Photo	Yes
Image Area (pixels)	DX-format (L) 6,000 x 4,000 (M) 4,496 x 3,000 (S) 2,992 x 2,000

▼ File System

File Format Still Images	Compressed 12-bit NEF (RAW) JPEG: JPEG-Baseline Compliant with fine (approx 1:4), Normal (approx 1:8) or Basic (approx 1:16) Compression NEF (RAW) + JPEG: Single Photograph Recorded in both NEF (RAW) and JPEG Formats
Storage Media	SD SDHC SDXC
Card Slot	1 Secure Digital (SD)
	DPOF (Digital Print Order Format) EXIF 2.3 (Exchangeable Image File Format for Digital Still Cameras)

▼ Viewfinder

Viewfinder	Eye-level Pentamirror Single-Lens Reflex viewfinder
Viewfinder Frame Coverage	95% Horizontal (Approx.)
Viewfinder Magnification	0.85x (Approx.)
Viewfinder Eyepoint	18mm (-1.0m ⁻¹)
Viewfinder Diopter Adjustment	-1.7 to +0.5m ⁻¹
Focusing Screen	Type B BriteView Clear Matte Mark VII screen
Reflex Mirror	Quick-return type

Feature	Specification
Mirror Lock Up	Yes (for image sensor cleaning)
▼ Lens	
Lens Aperture	Instant-return type
Lens Compatibility at a Glance***	AF-S Lens Required for Autofocus
Compatible Lenses	<p>AF NIKKOR for F3AF not Supported.</p> <p>AF-S, AF-I: All Functions Supported.</p> <p>AI-P NIKKOR: All Functions Supported Except Autofocus and 3D Color Matrix Metering II.</p> <p>Electronic rangefinder can be used if Maximum Aperture is f/5.6 or Faster.</p> <p>IX NIKKOR Lenses Cannot be Used.</p> <p>Non-CPU: Autofocus not supported. Can be used in mode M, but exposure meter does not function.</p> <p>Other AF NIKKOR: All Functions Supported Except autofocus and 3D Color Matrix Metering II.</p> <p>Type G or D AF NIKKOR: All Functions Supported Except Autofocus.</p> <p>Type D PC NIKKOR: All Functions Supported Except Autofocus and some Shooting Modes.</p>
▼ Shutter	
Shutter Type	Electronically controlled vertical-travel focal-plane
Shutter Speed	1/4000 to 30 sec.
Fastest Shutter Speed	1/4000 sec.
Slowest Shutter Speed	30 sec.
Flash Sync Speed	Up to 1/200 sec.
Shutter Release Modes	<p>Continuous</p> <p>Delayed remote</p> <p>Quick Response Remote Mode</p> <p>Quiet shutter-release</p> <p>Self-timer Mode</p> <p>Single-frame [S] mode</p>
Frame Advance Rate	Up to 5 fps (manual focus, mode M or S, shutter speed 1/250 sec or faster, and other settings at default values)
Top Continuous Shooting Speed at full resolution	5 frames per second
Self-timer	<p>2, 5, 10, 20 sec.; 1 to 9 exposures</p> <p><i>Timer duration electronically controlled</i></p>
▼ Exposure	
Exposure Metering System	TTL exposure metering using 420-pixel RGB sensor
Metering Method	<p>Center-weighted: Weight of 75% given to 8 mm circle in center of frame</p> <p>Matrix: 3D color matrix metering II (type G and D lenses); color matrix metering II (other CPU lenses)</p> <p>Spot: Meters 3.5 mm circle (about 2.5% of frame) centered on selected focus point</p>
Metering Range	<p>0 to 20 EV (Matrix or center-weighted metering at ISO 100 equivalent, f/1.4 lens, at 20°C/68°F)</p> <p>2 to 20 EV (Spot metering at ISO 100 equivalent, f/1.4 lens at 20°C/68°F)</p>
Exposure Meter Coupling	CPU

Exposure meter coupling	On
Exposure Modes	Aperture-Priority (A) Auto Auto (flash off) Manual (M) Programmed Auto with flexible Program (P) Shutter-Priority Auto (S)
Scene Modes	Auto Auto [Flash Off] Child Close-up Landscape Night Portrait Portrait Sports
Exposure Compensation	±5 EV in increments of 1/3EV
Exposure Lock	Luminosity locked at detected value with AE-L/AF-L button
Picture Control	Landscape Monochrome Neutral Portrait Selected Picture Control can be Modified Standard Vivid
▼ Sensitivity	
ISO Sensitivity	ISO 100 -12,800 Hi-1 (ISO 25,600)
Lowest Standard ISO Sensitivity	100
Highest Standard ISO Sensitivity	12,800
Highest Expanded ISO Sensitivity	1 EV above ISO 12800 (ISO 25600 equivalent)
Expanded ISO Sensitivity Options	1 EV above ISO 12800 (ISO 25600 equivalent) Auto ISO sensitivity control available
High ISO Noise Reduction	Low Normal High Off
Active D-Lighting	On Off
▼ Focus/Autofocus	
Single-point AF mode	Yes
Dynamic AF Mode	Number of AF points: 11 (3D-tracking)
Auto-area AF Mode	Yes
Autofocus System	Nikon Multi-CAM 1000 autofocus sensor module with TTL phase detection
Detection Range	-1 to 19 EV (ISO 100, 68°F/20°C)
Lens Servo	Autofocus (AF): Single-servo AF (AF-S); Continuous-servo AF (AF-C); auto AF-S/AF-C selection (AF-A); predictive focus tracking activated automatically according to subject status

	Manual focus (MF): Electronic rangefinder can be used
Focus Lock	Focus can be locked by pressing AE-L/AF-L button Focus can be locked by pressing shutter-release button halfway (single-servo AF)
Focus Modes	Auto AF-S/AF-C selection (AF-A) Continuous-servo (AF-C) Face-Priority AF available in Live View only and D-Movie only Full-time Servo (AF-A) available in Live View only and D-Movie only Manual (M) with electronic rangefinder Normal area available in Live View and D-Movie only Predictive focus tracking activated automatically according to subject status Single-servo AF (AF-S) Wide area available in Live View and D-Movie only
Maximum Autofocus Areas/Points	11
Autofocus Sensitivity	-1 to +19 EV (ISO 100, 20°C/68°F)
▼ Flash	
Built-in Flash	Yes
X-Sync Speed	1/200
Flash Control	TTL: i-TTL flash control using 420-pixel RGB sensor is available with built-in flash and SB-910, SB-900, SB-800, SB-700, SB-600, SB-400 or SB-300; i-TTL balanced fill-flash for digital SLR is used with matrix and center-weighted metering, standard i-TTL flash for digital SLR with spot metering
Flash Sync Modes	Auto Auto with red-eye reduction Auto slow sync Auto slow sync with red-eye reduction Fill-flash Rear-curtain sync Rear-curtain with slow sync Red-Eye reduction Red-Eye reduction with slow sync Slow sync Off
Flash Compensation	-3 to +1 EV in increments of 1/3 EV
Flash-ready Indicator	Lights when built-in flash or optional flash unit such as SB-910, SB-900, SB-400, SB-300, SB-80DX, SB-28DX or SB-50DX is fully charged
Accessory Shoe	Yes
Nikon Creative Lighting System (CLS)	CLS Supported
Flash Sync Terminal	Sync Terminal Adapter AS-15 (available separately)
▼ White Balance	
White Balance	Auto Cloudy Direct Sunlight Flash Fluorescent (7 types) Incandescent Preset Manual Shade
▼ Live View	

Live View Shooting	Yes
Live View Lens servo	Autofocus (AF): Single-servo AF (AF-S); full-time-servo AF (AF-F) Manual focus (MF)
Live View AF-area mode	Face-priority AF Wide-area AF Normal-area AF Subject-tracking AF
Live View Autofocus	Contrast-detect AF anywhere in frame (camera selects focus point automatically when face-priority AF or subject-tracking AF is selected)
	Auto (flash off) mode
▼ Movie	
Movie Metering	TTL exposure metering using main image sensor
Movie Maximum recording time	20 min.
Movie File Format	MOV
Movie Video Compression	H.264/MPEG-4 Advanced Video Coding
Movie Audio recording format	Linear PCM
Movie	Full HD 1,920x1,080 / 60 fps Full HD 1,920x1,080 / 50 fps Full HD 1,920x1,080 / 30 fps Full HD 1,920x1,080 / 25 fps Full HD 1,920x1,080 / 24 fps HD 1,280x720 / 60 fps HD 1,280x720 / 50 fps VGA 640x424 / 30 fps VGA 640x424 / 25 fps
Movie Audio	Built-in microphone, monaural Optional external stereo mini-pin jack (3.5mm diameter) Microphone sensitivity can be adjusted
▼ Monitor	
Monitor Size	3.0 in. diagonal
Monitor Resolution	921,000 Dots
Monitor Type	Wide Viewing Angle TFT-LCD
Monitor Angle of View	160-degree wide-viewing angle
▼ Playback	
Playback Functions	Auto Image Rotation Full-Frame and Thumbnail (4, 9, or 72 images or calendar) Histogram Display Image Comment Movie Playback Playback with Zoom Slideshow
In-Camera Image Editing	Color Balance

in-camera image editing	Color Balance
	Color Outline
	Color Sketch
	D-Lighting
	Distortion Control
	Filter Effects
	Fisheye
	Image Overlay
	Miniature Effect
	Monochrome
	NEF (RAW) Processing
	Perspective Control
	Photo Illustration
	Quick Retouch
	Red-Eye Correction
	Resize
	Selective Color
	Straighten
	Trim

▼ Interface

Interface	Accessory Terminal: Remote Cord: MC-DC2 (available separately); GPS unit: GP-1A (available separately) Audio input: Stereo mini-pin jack (3.5-mm diameter) HDMI output: Type C mini-pin HDMI connector Hi-speed USB Video Output: NTSC, PAL
Wi-Fi Functionality	Eye-Fi Compatible
GPS	GP-1A GPS unit

▼ Menus

Recent Settings	Yes
Supported Languages	Arabic Bengali Brazilian Portuguese Chinese (Simplified and Traditional) Czech Danish Dutch English Finnish French German Greek Hindi Hungarian Indonesian Italian Japanese Korean Marathi Norwegian Persian Polish Portuguese Romanian Russian Spanish Swedish Tamil Telugu Thai Turkish Vietnamese

	Ukrainian Vietnamese
Date, Time and Daylight Savings Time Settings	Yes
World Time Setting	Yes

▼ Power

Battery / Batteries	EN-EL14a Rechargeable Li-ion Battery
Battery Life (shots per charge)	700 shots (CIPA)
AC Adapter	EH-5b AC Adapter; requires EP-5A Power Connector (available separately)
Battery Charger	MH-24 Quick Charger

▼ Miscellaneous

Tripod Socket	1/4 in.
Approx. Dimensions (Width x Height x Depth)	4.9 in. (124 mm) x 3.9 in. (98 mm) x 3.0 in. (75.5 mm)
Approx. Weight	14.5 oz. (410 g) <i>camera body only</i>
Operating Environment	0–40 °C (+32–104 °F) Less than 85% (no condensation)