

Integrated DVR	
Functionality	Simplex
Video Compression	MPEG-4
Resolution	640 x 480, 320 x 240
Recording Frame Rate	320x240: 1~30FPS, 640 x 480: 1~12FPS
Recording Resolution	VGA (640x480)/ QVGA (320x240)
Recording Qualities	High, Medium, Low
Recording Modes	Manual/ Schedule/ Motion Detection
Recording Media	SD1.1/2.0 SD/SDHC Card, Max 32GB
Video Format	NTSC/PAL
Video Display Output	1 CH RCA Composite
Live Viewing	Single Screen
Live Resolution	640 x 480
Live Frame Rate	30FPS
Play Search Mode	By Date, Time
Play Speed	Forward/Rewind:x1/x2/x4/x8/x16/x32
Play Mode	Single Screen
OSD & System Menu Display	Yes
OSD Language Display	English
Time & Date Stamp Display	Yes
Disk Full Warning	Full Stop / Overwrite (Selectable)
LED Indicators	Power, Record, Play, Menu
Battery Operable	Yes, 4 x AA
Battery Life	up to 12 Hours (lithium batteries)
Power Input	DC 12V ~ 180mA
Power Adapter Input	AC 110 ~ 240V (switching mode)
Dimensions	5" x 3" x 3"
Integrated Camera	
Image Sensor	1/6" Color CMOS Sensor
Resolution	640 x 480
Outdoor Use	No
Focal Length	Board Lens f3.62mm / F2.8
Focus Type	Fixed
Min. Illumination	2 lux
Motion Detection	Yes
Viewing Angle	66°

White Balance	Auto
Signal/Noise Ratio	46 dB
Optimum Focal Distance	10-15 ft