

Technical Specifications

Sound

Sound Enhancement	• Virtual Surround Sound • Treble and Bass Control
Sound System	Dolby Digital
Speaker output power	15 W x 2
Subwoofer output power	30 W
Total Power RMS @ 30% THD	60 W

Connectivity

Integrated Connections	Bluetooth
Side Connections	• Audio In (3.5mm) • USB
iPod/iPhone	• via 3.5mm Audio In • via bluetooth
Rear Connections	• Digital optical in • Subwoofer out • AUX in • Digital coaxial in

Sustainability

Packaging	• 80% recycled corrugated board • Soya based ink
-----------	--

Loudspeakers

Loudspeaker types	Integrated with main unit
Speaker Drivers per side	• 1 woofer • 1 Mylar tweeter
Speaker Impedance	4 ohm
Tweeter Impedance	8 ohm
Subwoofer type	Passive
Subwoofer driver	1 x 5.25" woofer
Subwoofer freq range	45 - 200 Hz
Subwoofer impedance	8 ohm

Design

Wall mountable	Yes
----------------	-----

Power

Power consumption	30 W
Power supply	110-127V / 220-240V, ~50-60Hz
Standby power consumption	< 0.5 W

Dimensions

Main Unit (W x H x D)	800 x 52.4 x 75.6 mm
Main Unit Weight	1.2 kg
Subwoofer (W x H x D)	165 x 240 x 295 mm
Subwoofer Weight	2.6 kg
Subwoofer cable length	3 m
Packaging (W x H x D)	400 x 292 x 349 mm
Weight incl. Packaging	5.4 kg