

DISPLAY	Type	1.4 cm / 0.55" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024x768 (Native) / SXGA 1280x1024 (compressed)
	Lens	1.2x Manual optical zoom / Manual optical focus
	Zoom Factor	N/A
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Display Size	30"-300" / 0.8m-7.6m
	Throw Distance	1.2m-10m / 3.9ft. - 32.8ft.
	Throw Ratio	1.7-2.1:1
	Lamp Type	230 watt
	Lamp Life (normal/eco-mode)	4000 / 6000* hours
	Brightness	3,200 ANSI Lumens
	Contrast Ratio	3200:1 (dynamic)
	Aspect Ratio	4:3 (native) and 16:9
	Color Wheel	6-Seg RGBCYW / 7200rpm
	Color Depth	24 bits, 16.7M Colors (8+8+8)
	Color Gamut	85% NTSC 1931 CIE
INPUT SIGNAL	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM, SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25pfs and 30fps)
	Frequency	Fh: 31-100KHz, Fv: 50-120Hz
COMPATIBILITY	PC	VGA to SXGA
	Mac®	Up to 1152x864 (scaled)
CONNECTOR	Audio Input	3.5mm mini jack
	Audio Out	3.5mm mini jack
	Video Out	
	RGB Input	15-pin mini D-sub (x2)
	Composite Input	RCA jack
	S-Video Input	4-pin mini-DIN
	Component	N/A
	RGB Output	15-pin mini D-sub
	Control	RS-232 (9-pin D-sub) / RJ-45
	Digital	N/A
	Network	N/A
	USB	Type B (mouse control)
	Mic-In	N/A
	LAN	
	Screen Trigger	N/A
	Card Reader	N/A
AUDIO	Speakers	5W x 2
	Amplifier	N/A
POWER	Voltage	90-240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	305W (typ) / <1W (stand-by mode)
CONTROLS	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source
	OSD	Picture: brightest, contrast, color setting, keystone, aspect ratio, image, white intensity, gamma, 3D sync, 3D sync invert Computer Image: Frequency, tracking, H.

		position, V. position Video Image: Saturation, sharpness, tint Setting: Menu position, projection, signal type, lamp hour, lamp hour reset, filter mode, filter hours, filter hours reset, power saving, auto source, eco-mode, high altitude, OSD timeout Advance: blank screen, password, screen capture, start up screen Text shot: digital zoom, dynamic contrast ratio, close caption, BrilliantColor
OPERATING CONDITIONS	Temperature	32°-104° (0°C-40°C)
	Humidity	10%-90% (non-condensing)
	Altitude	0-6,000 ft (1,800m), operational up to 10,000 ft (3,048m)
NOISE LEVEL	Normal	34dB
	Eco-Mode	29dB
DIMENSIONS (WxHxD)	Physical	11 x 4.5 x 8.6 (in) / 280 x 114 x 218 (mm)
	Packaging	13.6 x 8.7 x 12 (in) / 345 x 305 x 220 (mm)
WEIGHT	Net	5.9 lb (2.68 kg)
	Gross	N/A
OPTIONAL ACCESSORIES	Wireless Presentation Gateway	
	Wireless Presentation Gateway	
	Dongle	Carrying Case
		3D Active Shutter Glasses Ceiling Mount Kit Cable Management
LANGUAGE	N/A	
Regulations	CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOM, PSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC	
PACKAGE CONTENTS	ViewSonic projector, carrying case, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)	