

Specifications

Model	LE49A6R9	
Panel size	49" class 48.50" diagonal (1232.0mm)	
Display method	Transmission TFT color LCD panel	
Number of Pixels	1920(H) × 1080(V)	
Broadcasting system	US system M ATSC standard (8VSB), QAM	
Receiving channels	VHF 2-13 UHF 14-69 CATV 14-36 (A)-(W) 37-59 (AA)-(WW) 60-85 (AAA)-(ZZZ) 86-94 (86)-(94) 95-99 (A-5)-(A-1) 100-135 (100)-(135) 01 (4A)	• Digital Terrestrial Broadcast(8VSB): 2-69 • Digital Cable (QAM): 1-135
Tuner type	Frequency synthesized	
Inputs	Video: 1.0 V (p-p), 75 ohms Audio: 2Vrms Max. Component video: (Y) 1.0 V (p-p), 75 ohms, (Pb)/(Pr) 0.7 V (p-p), 75 ohms HDMI: HDMI compliant (type A connector) HDCP compliant E-EDID compliant HDMI1.4a, ARC, CEC Scan rates: 480i, 480p, 720p, 1080i, 1080p MHL: MHL 1.4 PC Monitor: Mini-Dsub 15pin Antenna: VHF/UHF In 75 ohms coaxial	
Outputs	Digital audio (COAXIAL): 0.5 V (p-p), 75 ohms terminated Audio Out (3.5mm Stereo): 470 mVrms, 1k ohms	
Speakers	Downfiring. 157.5 mm × 40 mm x 37 mm 8 ohms × 2,	
Audio output power	8.0W + 8.0W	
Power supply	AC 120V, 60Hz	
Power consumption	Operation: 105W Standby: <1W	
Weight	9.6kg (21.2lbs)	
Dimensions	Width: 1099.5mm (43-5/16") Height: 688.0mm (27-1/8") Depth: 209.0mm (8-1/4")	
Operating temperature	5°C - 35°C	
Operating humidity	Less than 80% RH	
Accessories	Remote control AC cord Batteries (AAA) × 2 Stand x 2 (R, L), Stand Screws x 2 (M6 x 16) Owner's Guide Quick Start Guide Roku Ready Streaming Stick (Pre-inserted into HDMI3 input)	

- **Designs and specifications are subject to change without notice.**
- **For information on our other products, please visit our website at www.hitachi.us**