

Panel Type	IPS with LED backlight
Resolution	1920 x 1080 @ 60 Hz (Full HD)
Dynamic Contrast Ratio	10,000,000:1
Contrast Ratio (Typical)	1,000:1
Viewing Angles	Horizontal: 178° Vertical: 178°
Brightness	250 cd/m² (typical)
Color Gamut	72% (typical)
Pixel Pitch	88 pixels per inch
Response Time (Typical)	7 ms
Signal Inputs	VGA, HDMI, DVI-D, HDCP support
Power Supply	External power supply
Maximum Power Consumption	30 watts
Energy Saving Mode	< 0.5 watts
Tilt	-5° to 25° vertical
Detachable Base	Detachable base, ships attached
VESA Compatibility	None
Languages	German, Simplified Chinese, Traditional Chinese, Japanese, English, Spanish, French, Italian, Netherlands, Brazil, Portuguese

Certifications	Microsoft WHQL certification CB, CE, FCC marking, ErP, CSA/C-UL/C-ETL Mark, UL/CSA-NTRL/ETL-NRTL Mark, ICES, Argentina S-Ma Japan VCCI, CCC, China CEL, Taiwan BSMI, Bauart, CECP, ISO9241-307, GOST
LED Backlight	Mercury-free LED backlighting
Backlight Lamp Life	30,000 hours
Arsenic-Free Display Glass	Yes
Dimensions (HxWxD)	16.89 x 22.76 x 7.56" / 42.90 x 57.81 x 19.20 cm
Weight	9.71 lb / 4.40 kg