

Aircraft	Model	T600
	Weight (Battery Included)	2935 g
	Hovering Accuracy (GPS Mode)	Vertical: 0.5 m Horizontal: 2.5 m
	Max Angular Velocity	Pitch: 300°/s Yaw: 150°/s
	Max Tilt Angle	35°
	Max Ascent Speed	5 m/s
	Max Descent Speed	4 m/s
	Max Speed	22 m/s (ATTI mode, no wind)
	Max Flight Altitude	4500 m
	Max Wind Speed Resistance	10 m/s
	Max Flight Time	Approximately 18 minutes
	Motor Model	DJI 3510
	Propeller Model	DJI 1345
	Indoor Hovering	Enabled by default
	Operating Temperature Range	-10° to 40° C
	Diagonal Distance	559 to 581 mm
	Dimensions	438x451x301 mm
Gimbal	Model	ZENMUSE X3
	Output Power (With Camera)	Static: 9 W In Motion: 11 W
	Operating Current	Station: 750 mA Motion: 900 mA
	Angular Vibration Range	±0.03°
	Mounting	Detachable
	Controllable Range	Pitch: -90° to +30° Pan: ±320°
	Mechanical Range	Pitch: -125° to +45° Pan: ±330°
	Max Controllable Speed	Pitch: 120°/s Pan: 180°/s
Camera	Name	X3
	Model	FC350
	Total Pixels	12.76M
	Effective Pixels	12.4M

	Image Max Size	4000x3000
	ISO Range	100-3200 (video) 100-1600 (photo)
	Electronic Shutter Speed	8s — 1/8000s
	FOV (Field Of View)	94°
	CMOS	Sony EXMOR 1/2.3"
	Lens	20mm (35mm format equivalent)f/2.8 focus at ∞ 9 Elements in 9 groups Anti-distortion
	Still Photography Modes	Single shoot Burst shooting: 3/5/7 frames Auto Exposure Bracketing (AEB): 3/5 bracketed frames at 0.7EV Bias Time-lapse
	Video Recording Modes	UHD (4K): 4096x2160p24/25, 3840x2160p24/25/30 FHD: 1920x1080p24/25/30/48/50/60 HD: 1280x720p24/25/30/48/50/60
	Max Bitrate Of Video Storage	60 Mbps
	Supported File Formats	FAT32/exFAT Photo: JPEG, DNG Video: MP4/MOV (MPEG-4 AVC/H.264)
	Supported SD Card Types	Micro SD Max capacity: 64 GB. Class 10 or UHS-1 rating required.
	Operating Temperature Range	0° to 40° C
Remote Controller	Name	C1
	Operating Frequency	922.7~927.7 MHz (Japan Only) 5.725~5.825 GHz 2.400~2.483 GHz
	Transmitting Distance (Outdoor And Unobstructed)	2 km
	EIRP	10dBm@900m, 13dBm@5.8G, 20dBm@2.4G
	Video Output Port	USB, mini-HDMI
	Power Supply	Built-in battery
	Charging	DJI charger
	Dual User Capability	Host-and-Slave connection
	Mobile Device Holder	Tablet or Phone
	Max Mobile Device Width	170mm
	Output Power	9 W
	Operating Temperature Range	-10° to 40° C
	Storage Temperature Range	Less than 3 months: -20° to 45° C More than 3 months: 22° to 28° C
	Charging Temperature Range	0-40° C
	Battery	6000 mAh LiPo 2S
Charger	Model	A14-100P1A

	Voltage	26.3 V
	Rated Power	100 W
Battery (Standard)	Name	Intelligent Flight Battery
	Model	TB47
	Capacity	4500 mAh
	Voltage	22.2 V
	Battery Type	LiPo 6S High voltage battery
	Energy	99.9 Wh
	Net Weight	570 g
	Operating Temperature Range	-10° to 40° C
	Storage Temperature Range	Less than 3 months: -20° to 45° C More than 3 months: 22° C to 28° C
	Charging Temperature Range	0° to 40° C
	Max Charging Power	180 W

Vision Positioning	Velocity Range	Below 8 m/s (2 m above ground)
	Altitude Range	5-500 cm
	Operating Environment	Brightly lit (lux > 15) patterned surfaces
	Operating Range	0-250 cm
DJI GO App	Mobile Device System Requirements	iOS 8.0 or later



Supported Mobile Devices

* Compatible with iPhone 5s, iPhone 6, iPhone 6 Plus, iPad Air, iPad Air Wi-Fi + Cellular, iPad mini 2, iPad mini 2 Wi-Fi + Cellular, iPad Air 2, iPad Air 2 Wi-Fi + Cellular, iPad mini 3, and iPad mini 3 Wi-Fi + Cellular. This app is optimized for iPhone 5s, iPhone 6, and iPhone 6 Plus.
Android version coming soon.