

System Specifications

Wireless Standard

- IEEE 802.11 b/g/n

Wireless Transfer Rate

- Receive: 300 Mbps*
- Transmit: 300 Mbps*

Wireless Security

- 64/128 bit WEP, WPA-PSK/WPA2-PSK

WLAN Features

- Universal repeater mode
- Wi-Fi Protected Setup (WPS)
- Wi-Fi Multimedia (WMM)
- Wireless output power management
- MAC address filtering

Hardware Specifications

- One 10/100 Mbps Ethernet RJ-45 port with auto MDI/MDIX support
- LED indicator:
 - ◊ Signal strength
 - ◊ Wireless
 - ◊ Power
 - ◊ WPS
 - ◊ Ethernet
- Two 2 dBi internal antennas
- Button/Switch:
 - ◊ WPS button
 - ◊ Power on/off switch
- Power rating: 5 V DC, 1.2 A
- Power consumption: 3 watt max.
- Plug type:
 - ◊ EU type: Two pins for EU 220 V to 230 V
 - ◊ US type: Two pins for US 120 V



LED indicators
(from top to bottom)

- Signal strength
- Wireless
- Power
- WPS
- Ethernet

WPS button

Power on/off
switch

Fast Ethernet port

Physical Specifications

- Item dimensions (W x D x H): 46 x 42 x 73 mm (1.81" x 1.59" x 2.87")
- Item weight: 85 g (0.18 lb.)
- Packing dimensions (W x D x H): 155 x 75 x 135 mm (6.10" x 2.95" x 5.31")
- Packing weight: 250 g (0.55 lb.)

Environmental Specifications

- Operating environment
 - Temperature: 0°C to 40°C (32°F to 104°F)
 - Humidity: 10% to 90% (Non-condensing)
- Storage environment
 - Temperature: -30°C to 70°C (-22°F to 158°F)
 - Humidity: 10% to 95% (Non-condensing)

Certification

- Safety: CE LVD
- EMC: CE, FCC