

Max. Link Rate	Up to 150Mbps
Antenna Form Factor	Internal integrated
LED	1x network status LED, 1x WPS LED
Compliant Standard(s)	IEEE 802.11b , IEEE 802.11g , IEEE 802.11n Windows 7, Mac, Wi-Fi
Data Link Protocol(s)	Ethernet , IEEE 802.11b , IEEE 802.11g , IEEE 802.11n
Form Factor	Vertical
Integrated Switch	4-port switch
Network Transport Protocol	IPSec , L2TP , PPPoE , PPTP , TCP/IP
Remote Management Browser Support	Internet Explorer® 7 and above, Firefox® , or Safari®
WPS Push Button Security	true true
Authentication Method(s)	Radio Service Set ID (SSID)
Encryption Type(s) Supported	128-bit WEP , 256-bit WPA , 64-bit WEP , WPA2
Firewall	NAT and SPI
Interface Connector Type	RJ-45
Remote Management Protocol	HTTP
Interface	Ethernet 10Base-T/100Base-(4)
Radio Frequency Band1	2.4 Ghz
Operating Humidity	Operating: 10 ~ 85% non-condensing Storing: 5 ~ 95% non-condensing
Operating Temperature	Operating: 0~ 40C (32 ~ 104 F) Storing: -20 ~ 65 C (-13 ~ 155 F)
Adapters Cables Included	Power Supply, Networking Cable