

Type	Belt drive turntable, fully automatic
Motor	DC servo-controlled
Speeds	33-1/3 RPM, 45 RPM
Turntable Platter	Aluminum
Wow and Flutter	Less than 0.25% (WTD) @ 3 kHz (JIS)
Signal-to-Noise Ratio	>50 dB (DIN-B)
Output Level	Pre-amp "PHONO": 2.5 mV nominal at 1 kHz, 5 cm/sec Pre-amp "LINE": 150 mV nominal at 1 kHz, 5 cm/sec
Phono Pre-Amp Gain	36 dB nominal, RIAA equalized
USB Function	A/D, D/A: 16 bit 44.1 kHz or 48 kHz USB selectable Computer interface: USB 1.1 Compliant Windows XP, Vista or MAC OSX
Power Supply Requirements	120V AC, 60 Hz, 3W
Dimensions	360.0 mm (14.17") W x 97.5 mm (3.84") H x 356.0 mm (14.02") D
Weight	3 kg (6.6 lbs.)
Accessories Included	Dual RCA (female) to 3.5 mm (1/8") mini-plug (male) stereo adapter cable; dual RCA (female) to 3.5 mm (1/8") mini-plug (female) stereo adapter cable; 45 RPM adapter; USB cable; recording software

Replacement Stylus: ATN3600L